



## Safety Data Sheet

Copyright, 2020, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

<b>Document Group:</b>	23-3022-3	<b>Version Number:</b>	5.04
<b>Issue Date:</b>	03/30/20	<b>Supersedes Date:</b>	12/20/19

### SECTION 1: Identification

#### 1.1. Product identifier

3M™ DESK & OFFICE CLEANER 573

#### Product Identification Numbers

ID Number	UPC	ID Number	UPC
70-0051-5274-2	500-21200-10384-1	70-0714-9577-7	500-21200-10384-6
7000048018			

#### 1.2. Recommended use and restrictions on use

##### Recommended use

Aerosol foam cleaner for office surfaces.

#### 1.3. Supplier's details

<b>MANUFACTURER:</b>	3M
<b>DIVISION:</b>	Stationery and Office Supplies Division
<b>ADDRESS:</b>	3M Center, St. Paul, MN 55144-1000, USA
<b>Telephone:</b>	1-888-3M HELPS (1-888-364-3577)

#### 1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

### SECTION 2: Hazard identification

#### 2.1. Hazard classification

Gas Under Pressure: Liquefied gas.  
Simple Asphyxiant.  
Specific Target Organ Toxicity (single exposure): Category 1.

#### 2.2. Label elements

##### Signal word

Danger

##### Symbols

Gas cylinder | Health Hazard |

**Pictograms****Hazard Statements**

Contains gas under pressure; may explode if heated.

May displace oxygen and cause rapid suffocation.

Causes damage to organs:  
cardiovascular system |

**Precautionary Statements****Prevention:**

Do not breathe dust/fume/gas/mist/vapors/spray.  
Do not eat, drink or smoke when using this product.  
Wash thoroughly after handling.

**Response:**

IF exposed: Call a POISON CENTER or doctor/physician.  
Specific treatment (see Notes to Physician on this label).

**Storage:**

Protect from sunlight. Store in a well-ventilated place.  
Store locked up.

**Disposal:**

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

**Notes to Physician:**

Exposure may increase myocardial irritability. Do not administer sympathomimetic drugs unless absolutely necessary.

**Supplemental Information:**

May cause frostbite. Intentional concentration and inhalation may be harmful or fatal.

**SECTION 3: Composition/information on ingredients**

Ingredient	C.A.S. No.	% by Wt
WATER	7732-18-5	85 - 95
ISOPROPYL ALCOHOL	67-63-0	3 - 5 Trade Secret *
ISOBUTANE PROPELLANT	75-28-5	1 - 5 Trade Secret *
ETHOXYLATED ALCOHOLS	68439-46-3	1 - 3 Trade Secret *
SODIUM CARBONATE	497-19-8	0.1 - 1
FRAGRANCE	Trade Secret*	< 0.5

\*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

**SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

**Inhalation:**

Remove person to fresh air. Get medical attention.

**Skin Contact:**

Thaw frosted skin with lukewarm water. Do not rub affected area. Get medical attention.

**Eye Contact:**

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

**If Swallowed:**

Rinse mouth. If you feel unwell, get medical attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

#### 4.3. Indication of any immediate medical attention and special treatment required

Exposure may increase myocardial irritability. Do not administer sympathomimetic drugs unless absolutely necessary.

## SECTION 5: Fire-fighting measures

#### 5.1. Suitable extinguishing media

Use a fire fighting agent suitable for the surrounding fire.

#### 5.2. Special hazards arising from the substance or mixture

None inherent in this product.

#### Hazardous Decomposition or By-Products

**Substance**

Hydrocarbons  
Carbon monoxide  
Carbon dioxide

**Condition**

During Combustion  
During Combustion  
During Combustion

#### 5.3. Special protective actions for fire-fighters

No special protective actions for fire-fighters are anticipated.

## SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

#### 6.2. Environmental precautions

Avoid release to the environment.

#### 6.3. Methods and material for containment and cleaning up

If possible, seal leaking container. Place leaking containers in a well-ventilated area, preferably an operating exhaust hood, or if necessary outdoors on an impermeable surface until appropriate packaging for the leaking container or its contents is available. Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or

commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with detergent and water. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Do not use in a confined area with minimal air exchange. Do not pierce or burn, even after use. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling.

### 7.2. Conditions for safe storage including any incompatibilities

Protect from sunlight. Store in a well-ventilated place. Store away from heat. Do not expose to temperatures exceeding 50 C/ 122 F.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
ISOPROPYL ALCOHOL	67-63-0	ACGIH	TWA:200 ppm;STEL:400 ppm	A4: Not class. as human carcin
ISOPROPYL ALCOHOL	67-63-0	OSHA	TWA:980 mg/m3(400 ppm)	
ISOBUTANE PROPELLANT	75-28-5	ACGIH	STEL:1000 ppm	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

### 8.2. Exposure controls

#### 8.2.1. Engineering controls

Do not remain in area where available oxygen may be reduced. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

#### 8.2.2. Personal protective equipment (PPE)

##### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Full Face Shield

Indirect Vented Goggles

##### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the

substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended: Polymer laminate

### Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece supplied-air respirator

For questions about suitability for a specific application, consult with your respirator manufacturer.

### Thermal hazards

Wear cold insulating gloves/face shield/eye protection.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

#### Appearance

Physical state

Liquid

Color

White

Specific Physical Form:

Foam

Odor

Clean, Fresh Odor

Odor threshold

No Data Available

pH

11 - 12

Melting point

Not Applicable

Boiling Point

180 - 213 °F

Flash Point

No flash point

Evaporation rate

>=1 [Ref Std:WATER=1] [Details:product as applied (without propellant)]

Flammability (solid, gas)

Not Applicable

Flammable Limits(LEL)

1.80 % [Details:for propellant]

Flammable Limits(UEL)

12.7 % [Details:for propellant]

Vapor Pressure

31 - 43 psi [@ 70 °F] [Details:(aerosol can pressure)]

Vapor Density

No Data Available

Density

1 g/ml

Specific Gravity

Approximately 1 [Ref Std:WATER=1]

Solubility In Water

No Data Available

Solubility- non-water

No Data Available

Partition coefficient: n-octanol/ water

No Data Available

Autoignition temperature

No Data Available

Decomposition temperature

No Data Available

Viscosity

Not Applicable

Volatile Organic Compounds

5.77 % weight

Percent volatile

96 - 98 % weight

VOC Less H2O & Exempt Solvents

No Data Available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

This material is considered to be non reactive under normal use conditions.

**10.2. Chemical stability**

Stable.

**10.3. Possibility of hazardous reactions**

Hazardous polymerization will not occur.

**10.4. Conditions to avoid**

Heat

Sparks and/or flames

**10.5. Incompatible materials**

Not determined

**10.6. Hazardous decomposition products****Substance****Condition**

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

**SECTION 11: Toxicological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

**11.1. Information on Toxicological effects****Signs and Symptoms of Exposure**

**Based on test data and/or information on the components, this material may produce the following health effects:**

**Inhalation:**

Simple Asphyxiation: Signs/symptoms may include increased heart rate, rapid respirations, drowsiness, headache, incoordination, altered judgement, nausea, vomiting, lethargy, seizures, coma, and may be fatal.

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May cause additional health effects (see below).

**Skin Contact:**

Frostbite: Signs/symptoms may include intense pain, discoloration of skin, and tissue destruction.

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness.

**Eye Contact:**

Frostbite: Signs/symptoms may include intense pain, clouding of the cornea, redness, swelling, and blindness.

Contact with the eyes during product use is not expected to result in significant irritation.

**Ingestion:**

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

#### Additional Health Effects:

#### Single exposure may cause target organ effects:

Single exposure, above recommended guidelines, may cause:

Cardiac Sensitization: Signs/symptoms may include irregular heartbeat (arrhythmia), faintness, chest pain, and may be fatal.

#### Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

#### Acute Toxicity

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
ISOPROPYL ALCOHOL	Dermal	Rabbit	LD50 12,870 mg/kg
ISOPROPYL ALCOHOL	Inhalation-Vapor (4 hours)	Rat	LC50 72.6 mg/l
ISOPROPYL ALCOHOL	Ingestion	Rat	LD50 4,710 mg/kg
ISOBUTANE PROPELLANT	Inhalation-Gas (4 hours)	Rat	LC50 276,000 ppm
ETHOXYLATED ALCOHOLS	Dermal	Rabbit	LD50 > 2,000 mg/kg
ETHOXYLATED ALCOHOLS	Ingestion	Rat	LD50 1,378 mg/kg
SODIUM CARBONATE	Dermal	Rabbit	LD50 > 2,000 mg/kg
SODIUM CARBONATE	Ingestion	Rat	LD50 2,800 mg/kg

ATE = acute toxicity estimate

#### Skin Corrosion/Irritation

Name	Species	Value
ISOPROPYL ALCOHOL	Multiple animal species	No significant irritation
ISOBUTANE PROPELLANT	Professional judgement	No significant irritation
ETHOXYLATED ALCOHOLS	Rabbit	Irritant
SODIUM CARBONATE	Rabbit	No significant irritation

#### Serious Eye Damage/Irritation

Name	Species	Value
ISOPROPYL ALCOHOL	Rabbit	Severe irritant
ISOBUTANE PROPELLANT	Professional judgement	No significant irritation
ETHOXYLATED ALCOHOLS	Professional judgement	Corrosive
SODIUM CARBONATE	Rabbit	Corrosive

#### Skin Sensitization

Name	Species	Value
ISOPROPYL ALCOHOL	Guinea pig	Not classified

ETHOXYLATED ALCOHOLS	Guinea pig	Not classified
----------------------	------------	----------------

### Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

### Germ Cell Mutagenicity

Name	Route	Value
ISOPROPYL ALCOHOL	In Vitro	Not mutagenic
ISOPROPYL ALCOHOL	In vivo	Not mutagenic
ISOBUTANE PROPELLANT	In Vitro	Not mutagenic
ETHOXYLATED ALCOHOLS	In Vitro	Not mutagenic
SODIUM CARBONATE	In Vitro	Not mutagenic

### Carcinogenicity

Name	Route	Species	Value
ISOPROPYL ALCOHOL	Inhalation	Rat	Some positive data exist, but the data are not sufficient for classification

### Reproductive Toxicity

#### Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
ISOPROPYL ALCOHOL	Ingestion	Not classified for development	Rat	NOAEL 400 mg/kg/day	during organogenesis
ISOPROPYL ALCOHOL	Inhalation	Not classified for development	Rat	LOAEL 9 mg/l	during gestation
ETHOXYLATED ALCOHOLS	Dermal	Not classified for female reproduction	Rat	NOAEL 250 mg/kg/day	2 generation
ETHOXYLATED ALCOHOLS	Dermal	Not classified for development	Rat	NOAEL 250 mg/kg/day	2 generation
ETHOXYLATED ALCOHOLS	Dermal	Not classified for male reproduction	Rat	NOAEL 100 mg/kg/day	2 generation
SODIUM CARBONATE	Ingestion	Not classified for development	Mouse	NOAEL 340 mg/kg/day	during organogenesis

### Target Organ(s)

#### Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
ISOPROPYL ALCOHOL	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
ISOPROPYL ALCOHOL	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
ISOPROPYL ALCOHOL	Inhalation	auditory system	Not classified	Guinea pig	NOAEL 13.4 mg/l	24 hours
ISOPROPYL ALCOHOL	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse
ISOBUTANE PROPELLANT	Inhalation	cardiac sensitization	Causes damage to organs	Multiple animal species	NOAEL Not available	
ISOBUTANE PROPELLANT	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
ISOBUTANE PROPELLANT	Inhalation	respiratory irritation	Not classified	Mouse	NOAEL Not available	
ETHOXYLATED	Inhalation	respiratory irritation	Some positive data exist, but the	Not	NOAEL Not	not available



ALCOHOLS			data are not sufficient for classification	available	available	
----------	--	--	--	-----------	-----------	--

**Specific Target Organ Toxicity - repeated exposure**

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
ISOPROPYL ALCOHOL	Inhalation	kidney and/or bladder	Not classified	Rat	NOAEL 12.3 mg/l	24 months
ISOPROPYL ALCOHOL	Inhalation	nervous system	Not classified	Rat	NOAEL 12 mg/l	13 weeks
ISOPROPYL ALCOHOL	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 400 mg/kg/day	12 weeks
ISOBUTANE PROPELLANT	Inhalation	kidney and/or bladder	Not classified	Rat	NOAEL 4,500 ppm	13 weeks
ETHOXYLATED ALCOHOLS	Dermal	kidney and/or bladder   hematopoietic system	Not classified	Rat	NOAEL 125 mg/kg/day	13 weeks
SODIUM CARBONATE	Inhalation	respiratory system	Not classified	Rat	LOAEL 0.07 mg/l	3 months

**Aspiration Hazard**

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

**SECTION 12: Ecological information****Ecotoxicological information**

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

**Chemical fate information**

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

**SECTION 13: Disposal considerations****13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. Facility must be capable of handling aerosol cans. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

**EPA Hazardous Waste Number (RCRA):** D001 (Ignitable)

**SECTION 14: Transport Information**

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

**SECTION 15: Regulatory information**

## 15.1. US Federal Regulations

Contact 3M for more information.

### EPCRA 311/312 Hazard Classifications:

**Physical Hazards**

Gas under pressure

**Health Hazards**

Simple Asphyxiant

Specific target organ toxicity (single or repeated exposure)

## 15.2. State Regulations

Contact 3M for more information.

## 15.3. Chemical Inventories

The components of this material are in compliance with the China "Measures on Environmental Management of New Chemical Substance". Certain restrictions may apply. Contact the selling division for additional information.

The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

Contact 3M for more information.

## 15.4. International Regulations

Contact 3M for more information.

**This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.**

## SECTION 16: Other information

### NFPA Hazard Classification

**Health:** 3 **Flammability:** 1 **Instability:** 0 **Special Hazards:** None  
**Aerosol Storage Code:** 1

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

### HMIS Hazard Classification

**Health:** 4 **Flammability:** 1 **Physical Hazard:** 0 **Personal Protection:** X - See PPE section.

Hazardous Material Identification System (HMIS® IV) hazard ratings are designed to inform employees of chemical hazards in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations. HMIS® IV ratings are to be used with a fully implemented HMIS® IV program. HMIS® is a registered mark of the American Coatings Association (ACA).

**Document Group:** 23-3022-3 **Version Number:** 5.04  
**Issue Date:** 03/30/20 **Supersedes Date:** 12/20/19

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY

OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

**3M USA SDSs are available at [www.3M.com](http://www.3M.com)**